

Apraksts

V rt ba

Visp r j inform cija:

Izstr d juma nosaukums:	UPS 25-60 N 180
Izstr d juma Nr.:	P c piepras juma
EAN numurs:	P c piepras juma

Tehn.:

trums Nr.:	3
Faktiski apr in t pl sma:	0.53 m ³ /st
S k a rezult jošais s kn šanas augstums:	4.507 m
Maks. s kn. augstums:	60 dm
TF klase:	110
Apstiprin jumi pases datu pl ksn t :	CE,VDE,EAC

Materi li:

S k a korpus:	Ner sošais t rauds
	DIN W.-Nr. 1.4301
S k rats:	Kompoz ts, PES/PP

Uzst d šana:

Amb. max at 80 dgr C liquid:	40 °C
Maks. darba spiediens:	10 bar
Pievienojums:	G 1 1/2
Spiediena pak pe:	PN 10
Garums no viena pievienojuma l dz otram:	180 mm

Š idrums:

S kn jamais š idrums:	Apkures dens
Š idruma temperat ras diapazons:	2 .. 110 °C
Liquid temperature during operation:	60 °C
Bl vums:	983.2 kg/m ³
Kinem tisk viskozit te:	1 mm ² /s

Elektriskie dati:

leejas jauda 1. trum :	50 W
leejas jauda 2. trum :	55 W
Maks. pat r jam jauda:	60 W
T kla frekvence:	50 Hz
Nomin lais spriegums:	1 x 230 V
1 truma str va:	0.21 A
2 truma str va:	0.25 A
3 truma str va:	0.28 A
Kondensatora lielums - darb ba:	2.5 µF
Korpasa klase (IEC 34-5):	IP44
Izol cijas klase (IEC 85):	F
Motora aizsardz.:	NONE
Termisk aizsardz.:	Aizsardz ba p c tinumu pretest bas

Konrole:

Spai u k rbas poz.:	9H
---------------------	----

Citi:

Neto svars:	2.9 kg
Bruto svars:	3.1 kg
Pieg des tilpums:	0.004 m ³
Danish VVS No.:	VVS NO 380481061
Swedish RSK No.:	RSK NO 5803097
Finnish:	LVI NO 4615616
Norwegian NRF no.:	NRF NO 9042215

